

# PRODUCT DATA SHEET

## ROLFI ROLL RUBBER GRANULATE

### PRODUCT DESCRIPTION

The Rolfi roll forms a gap between the deck substructure and foundation/subsurface.



### ADVANTAGES

- Constructive timber protection
- Substructure height can be adjusted
- Uniform load distribution
- Small irregularities can be evened out
- Dampens footfall noise
- Can be individually cut to length

### APPLICATION IMAGE



The Rolfi Roll rubber granulate on concrete with wood.

# PRODUCT DATA SHEET

# ROLFI ROLL RUBBER GRANULATE

## MATERIAL

- PUR-bound rubber granulate mat, black, possibly with coloured inclusions.

## MATERIAL PROPERTIES

Specifications	Measuring method	Unit	Value
Volume weight		Kg/m <sup>3</sup>	720
Weight per unit area		Kg/m <sup>2</sup>	5,76
Tensile strength	DIN 1798	N/mm <sup>2</sup>	0,50
Elongation at break	DIN 1798	%	45
Pressure span at 25 %	DIN 3386-2	N/mm <sup>2</sup>	0,55
Temperature resistance		°C	-40 – 115
Fire behaviour	DIN 13501-1	Class E	

## PRODUCT TABLE

Art. no.	Product description	Height [mm]	Length [mm]	Width [mm]	PU
945561	Rolfi Roll rubber granulate	8	2015	70	10

If you are not familiar with how this product is used, and particularly with the product's intended use, please contact our Application Technology department (technik@eurotec.team).