



A glue down collection

These floors are available in **dryback, click and for stairs!**

Mix & match with Flexile glue down floors!

In the picture – herringbone: Forest / planks: Forest / tiles: Matterhorn

FLEXILE
inspired by Coretec®

Technical specifications

Level of use

23 - 33 - 42 (EN ISO 10874)

Geometrical characteristics

Conform (EN ISO 24342)

Mass per unit area

5500 g/m² (EN ISO 23997)

Castor chair resistance

Pass 25000 cycles (EN ISO 4918)

Effect of a furniture leg

No visible change (EN ISO 16581)

Residual indentation

≤ 0.10 mm (EN ISO 24343-1)

Dimensional stability

≤ 0.25% (EN ISO 23999)

Curling after exposure to heat

≤ 0.20 mm (EN ISO 23999)

Colour fastness to light

≥ 7 (EN ISO 105-B02)

Impact sound reduction

2 (ISO 10140-3 / EN 717-2)

Formaldehyde emission class

E1 (EN 16516)

VOC emissions

Under detection limits (EN 16516)

Content of pentachlorophenol

< 0.02 mg/kg (EN 12673)

Fire classification

Bfl - S1 (EN 13501-1)

Slip resistance

DS - R10 (EN 13893 - DIN 51130)

Chemical resistance

Excellent resistance (EN ISO 26987)

Underfloor heating

Suitable

(see: Underfloor heating guidelines)

Electrostatic performance

≤ 2 kV (EN 1815)

Thermal resistance

0,0098 m².K/W (ISO 8302)

Choose from no fewer than 20 floors

All Flexile floors are also available in click version and for stairs!



Specifications



Planks:

1228 x 188 mm

Herringbones (HB):

678 x 113 mm

Tiles:

914,4 x 457,2 mm



3 mm



0.55 mm



Naturals



Authentics